Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	715	(384/26,40-42).CCLS.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/01/10 12:43
L2	3	("2342946").URPN.	USPAT	OR	OFF	2006/01/10 14:33
L3	23	(US-20020061144-$).did. or (US-5788379-$ or US-5806985-$ or US-5938340-$ or US-6113273-$ or US-6179468-$ or US-6190047-$ or US-6290395-$ or US-6315451-$ or US-6371647-$ or US-6960022-$ or US-2356641-$ or US-2479653-$ or US-3178240-$ or US-3326032-$ or US-3537762-$ or US-3890017-$ or US-4738299-$ or US-5429438-$ or US-5522664-$).did. or (US-2212778-$ or US-2342946-$ or US-3212827-$).did.	US-PGPUB; USPAT; USOCR	OR	OFF	2006/01/10 17:20
L4	15	3 and adjust$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2006/01/10 17:29
L5	4	3 and adjust$4 and set same screw	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2006/01/10 18:18
L6	5	3 and adjust$4 and nut	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2006/01/10 18:20
L7	98	1 and (nut or insert near thread$3)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2006/01/10 18:21
L8	4237	(plastic or resin or polymer) with (nut or thread$3 near insert) and adjust$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2006/01/10 18:22
L9	1573	(plastic or resin or polymer) with (nut or thread$3 near insert) and adjust$4 and bearing	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2006/01/10 18:23

L10	40	(plastic or resin or polymer) with (thread$3 near insert) and adjust$4 and bearing	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2006/01/10 18:23
L11	10	("3392225").URPN.	USPAT	OR	OFF	2006/01/10 18:25
L12	6	4 and spring	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	OFF	2006/01/10 18:42